



By **GRANDSTONE**[®]
ETITONIE



ETITONIE

by **GRANDSTONE**[®]



TYRE CATALOGUE

TRUCK TIRE

TT78

FEATURES:

- Mainly for long haul application of steer and trailer wheel
- Applicable for high way and good road surface with high speed
- Five ribs with four straight grooves for precise handling and low noise
- Shallow tread reduced rolling resistance for improved fuel economy

SUITABLE CONDITIONS: Steer and trailer position / Highway



Size	Ply Rating	Tread Depth (mm)	Standard Rim	Speed Rating	Load Index	Max.Load(kgs)		Inflation Pressure (kpa)	New Tyre Inflated Dimension(mm)	
						Single	Double		Overall Diameter	Section Width
11R22.5	16	14.5	8.25	M	146/143	3000	2725	830	1054	279
11R24.5	16	14.5	8.25	M	149/146	3250	3000	830	1104	279
295/75R22.5	16	14.5	9.00	M	146/143	3000	2725	830	1014	298

TRUCK TIRE

TT18

FEATURES:

- Mainly for all position
- Suitable for various road surface
- Strong center tread blocks provide excellent all-weather traction.
- Advanced tread compound provides remarkable performance for long haul service.

SUITABLE CONDITIONS: All position / Mix road



Size	Ply Rating	Tread Depth (mm)	Standard Rim	Speed Rating	Load Index	Max.Load(kgs)		Inflation Pressure (kpa)	New Tyre Inflated Dimension(mm)	
						Single	Double		Overall Diameter	Section Width
11R22.5	16	14.5	8.25	M	146/143	3000	2725	830	1050	279
11R24.5	16	14.5	8.25	M	149/146	3250	3000	830	1100	279
12R22.5	18	14.5	9.00	M	152/149	3550	3250	930	1085	300
295/80R22.5	18	15.5	9	M	152/149	3550	3250	900	1044	296
315/80R22.5	20	15.5	9.00	M	156/150	4000	3350	850	1076	312

TRUCK TIRE

TT28

FEATURES:

- Mainly for drive wheel
- Suitable for high speed on good road surface application
- Wide tread lugs and solid close shoulder ribs improve traction, reduce irregular wear
- Extra strong casing design for enhanced durability

SUITABLE CONDITIONS: Drive position / Highway



Size	Ply Rating	Tread Depth (mm)	Standard Rim	Speed Rating	Load Index	Max.Load(kgs)		Inflation Pressure (kpa)	New Tyre Inflated Dimension(mm)	
						Single	Double		Overall Diameter	Section Width
11R22.5	16	20	8.25	M	146/143	3000	2725	830	1054	279
11R24.5	16	20	8.25	M	149/146	3250	3000	830	1104	279
295/75R22.5	16	20	9.00	M	146/143	3000	2725	830	1014	298

TRUCK TIRE

TT66

FEATURES:

- Mainly used for drive wheel, also applicable for steer wheel.
- Suitable for mining and bad roads with low speed.
- Deep block design for good wearability, cut and tear resistance.
- The new structural design of the bead with excellent load capacity.

SUITABLE CONDITIONS: All position / ON/OFF the road



Size	Ply Rating	Tread Depth (mm)	Standard Rim	Speed Rating	Load Index	Max.Load(kgs)		Inflation Pressure (kpa)	New Tyre Inflated Dimension(mm)	
						Single	Double		Overall Diameter	Section Width
11R22.5	16	20	8.25	G	146/143	3000	2725	830	1050	279
11R24.5	16	20	8.25	G	149/146	3250	3000	830	1100	279