

WINMAX





WM901

The main features:

- Application: All position, suitable for all kinds of road conditions.
- Super wear ability and heat radiating performance, outstanding breaking and driving performance with heavy loading ability.
- Suitable for short-medium-long distances on paved or unpaved roads.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDARD RIM	SECTION WIDTH(mm)	OA DIAMETER	MAX.PRES SURE (KPA/PSI)
7.00R16	118/114L	14PR	12.5	5.5	198	778	770
7.50R16	122/118L	14PR	12.5	6.5	215	805	770
8.25R16	128/124L	16PR	14	6.5	235	855	770
9.00R20	144/142K	16PR	15	7	259	1019	900
10.00R20	149/148L	18PR	16	7.5	278	1054	930
11.00R20	152/149L	18PR	16.5	8	293	1085	930
12.00R20	156/153K	20PR	17	8.5	315	1125	830
11R22.5	146/143L	18PR	15	8.25	293	1085	930
11R24.5	149/146L	18PR	15	8.25	279	1104	850
13R22.5	156/153K	20PR	16.5	9.75	300	1084	850
12.00R24	160/157K	20PR	17	8.5	315	1125	900
315/80R22.5	156/150L	20PR	15	9	312	1076	900



WM902

The main features:

- Application: All position, suitable for all kinds of road conditions.
- Super wear ability and heat radiating performance, outstanding breaking and driving performance with heavy loading ability.
- Suitable for short-medium-long distances on paved or unpaved roads.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDARD RIM	SECTION WIDTH(mm)	OA DIAMETER	MAX.PRES SURE (KPA/PSI)
10.00R20	149/148L	18PR	16	7.5	278	1054	930
11.00R20	152/149L	18PR	16.5	8	293	1085	930



WM903

The main features:

- Application: All position, suitable for all kinds of road conditions.
- Super wear ability and heat radiating performance, outstanding breaking and driving performance with heavy loading ability.
- Suitable for short-medium-long distances on paved or unpaved roads.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDARD RIM	SECTION WIDTH(mm)	OA DIAMETER	MAX.PRES SURE (KPA/PSI)
10.00R20	149/148L	18PR	16	7.5	278	1054	930
11.00R20	152/149L	18PR	16.5	8	293	1085	930
12.00R20	156/153K	20PR	17	8.5	315	1125	900



WM859

The main features:

- Application: All Position Wheels for long distance.
- New designed pattern, Suitable for well paved road condition with excellent durability.
- Standard load, Low heat build-up, High speed.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDARD RIM	SECTION WIDTH(mm)	OA DIAMETER	MAX.PRES SURE (KPA/PSI)
12.00R24	160/157K	20PR	15.5	8.5	315	1226	900



WM807

The main features:

- Lug and block pattern design improve traction, driving and braking performance.
- Special tread compound provides outstanding resistance to puncture and tearing.
- Reinforced carcass and bead design ensure excellent handling

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDA RD RIM	SECTION WIDTH(mm)	OA DIAMET ER	MAX.PRES SURE (KPA/PSI)
11R22.5	146/143L	16PR	23	8.25	279	1054	830
11R24.5	149/146J	18PR	23	8.25	279	1104	850



WM896

The main features:

- Application: Steer Wheel for long distance, also can be used as All Position pattern.
- New designed pattern, Suitable for well paved road condition with high speed level and excellent durability.
- Heavy loading capacity, Low heat build-up, High speed and Low

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDA RD RIM	SECTION WIDTH(mm)	OA DIAMET ER	MAX.PRES SURE (KPA/PSI)
315/80R22.5	156/150M	20PR	15	9	312	1076	900



WM969

The main features:

- Application: Drive Wheel for medium mileage load series.
- Open Shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- Excellent load capability, Longer mileage, Super Durability.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDA RD RIM	SECTION WIDTH(mm)	OA DIAMET ER	MAX.PRES SURE (KPA/PSI)
12R22.5	1152/149M	18PR	20	9	300	1084	930
295/75R22.5	146/143M	16PR	19.5	9	298	1014	900
295/80R22.5	154/149M	18PR	20	9	298	1044	900
315/70R22.5	156/150M	20PR	20	9	312	1014	850
315/80R22.5	157/154M	20PR	20	9	312	1076	900



WM582

The main features:

- Application: All Position Wheels for long distance.
- New designed pattern, Suitable for well paved road condition with excellent durability.
- Standard load, Low heat build-up, High speed.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDA RD RIM	SECTION WIDTH(mm)	OA DIAMET ER	MAX.PRES SURE (KPA/PSI)
12.00R24	160/157K	20PR	15.5	8.5	315	1226	900
315/80R22.5	156/150M	20PR	15	9	312	1076	900



WM923

The main features:

- Application: Steer Wheel for long distance, also can be used as All Position pattern.
- New designed pattern, Suitable for well paved road condition with high speed level and excellent durability.
- Heavy loading capacity, Low heat build-up, High speed and Low noise.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDARD RIM	SECTION WIDTH(mm)	OA DIAMETER	MAX.PRES SURE (KPA/PSI)
11R22.5	149/146M	18PR	14.5	8.25	279	1050	830
11R24.5	149/146M	18PR	14.5	8.25	279	1104	830



WM939

The main features:

- Application: Steer Wheel for long distance, also can be used as All Position pattern.
- New designed pattern, Suitable for well paved road condition with high speed level and excellent durability.
- Heavy loading capacity, Low heat build-up, High speed and Low noise.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDARD RIM	SECTION WIDTH(mm)	OA DIAMETER	MAX.PRES SURE (KPA/PSI)
315/80R22.5	156/150M	20PR	15	9	312	1076	900



WM941

The main features:

- Application: Drive Wheel for medium mileage loading series
- Close Shoulder designs, the block pattern offer excellent drive force and good braking performance on paved road condition.
- Excellent load capability, Longer mileage, Super Durability.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDARD RIM	SECTION WIDTH(mm)	OA DIAMETER	MAX.PRES SURE (KPA/PSI)
11R22.5	149/146M	18PR	20.5	8.25	279	1050	830
11R24.5	152/149M	18PR	20.5	8.25	279	1104	830



WM957

The main features:

- Application: Drive wheel, suitable for rough and common roads.
- Unique tread belt structure, tire tread compound with high wear -resistance and low heat generation.
- Special compounds for cut resistance, excellent traction, high anti-impact force.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDARD RIM	SECTION WIDTH(mm)	OA DIAMETER	MAX.PRES SURE (KPA/PSI)
11R22.5	146/143M	16PR	20.5	8.25	279	1050	830
295/80R22.5	152/148M	18PR	21.5	9	298	1044	850
12R22.5	152/148M	18PR	21	9	300	1084	850
315/80R22.5	156/150L	20PR	21.5	9	312	1076	850
13R22.5	156/150K	20PR	21.5	9.75	320	1124	875



WM869

The main features:

- Application: Drive Wheel for medium mileage load series.
- Open Shoulder designs, the block pattern offer excellent drive force and anti-peeling performance on paved and unpaved roads.
- Excellent load capability, Longer mileage, Super Durability.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDARD RIM	SECTION WIDTH(mm)	OA DIAMETER	MAX.PRES SURE (KPA/PSI)
11.00R20	152/149L	18PR	20.5	8	293	1085	930
12.00R20	156/153K	20PR	21	8.5	315	1125	900
13R22.5	156/150L	20PR	21.5	9.75	320	1124	875



WM916

The main features:

- Application: Trailer Wheel, Suitable for rough and common roads.
- Excellent traction and high wear-resistance.
- Ultra strong ground adhesiveness on snow field and muddy roads.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDARD RIM	SECTION WIDTH(mm)	OA DIAMETER	MAX.PRES SURE (KPA/PSI)
385/65R22.5	160K	20	16	11.75	389	1072	900



WM932

The main features:

- Application: Trailer Wheel, Suitable for highway and common road.
- With Super driving performance and braking performance, high wear-resistance and low heat generation.
- Superior anti-irregular wearing performance, with extra anti-side and wet skid resistance, excellent safety and comfort

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDARD RIM	SECTION WIDTH(mm)	OA DIAMETER	MAX.PRES SURE (KPA/PSI)
385/65R22.5	160K	20	16	11.75	389	1072	900



WM891

The main features:

- Application: Drive wheel, suitable for rough and common roads.
- Unique tread belt structure, tire tread compound with high wear-resistance and low heat generation.
- Special compounds for cut resistance, excellent traction, high anti-impact force.

SIZE	L/S INDEX	PLY RATING	TREAD DEPTH(mm)	STANDARD RIM	SECTION WIDTH(mm)	OA DIAMETER	MAX.PRES SURE (KPA/PSI)
315/80R22.5	156/153L	20PR	19.5	9	312	1076	850

WINMAX

